

ENGINEERING  
TOMORROW

*Danfoss*

# Data center **liquid cooling**

Liquid cooling solutions, designed specifically to meet the growing demands of today's data center.

**30** years

Danfoss has been setting the standard in liquid cooling for over 30 years.



# The power of **Water**

It's better at **cooling**

**1,000x**

more cooling capacity

**25x**

better heat transfer

**10x**

less energy use

It's better for **your business**

**40%**

energy use reduction

**Greater**

chip density, with fewer racks

**Easier**

to maintain than immersion cooling

It's better for **the environment**

**Smaller**

carbon footprint

**Minimal**

water use

**Reduced**

refrigeration

## Why **liquid cooling?**

**For increased performance, energy efficiency and cost savings,** there is simply no substitute for direct-to-chip liquid cooling. No other system unlocks the full potential of your data center while simplifying installation and maintenance like Danfoss fluid conveyance solutions.

### **Energy sustained**

Danfoss' direct-to-chip liquid cooling improves data center Power Usage Effectiveness (PUE) by efficiently and cost-effectively removing heat emitted by a server processor.

### **Performance unleashed**

The thermal efficiency and reduced space requirements of liquid cooling enables increased chip density, unlocking your data center's full potential. Danfoss' hoses and connectors route coolant from the source to the chip, keeping your high-performing processors running smoothly, even during peak loads. That means consistent computing power and increased performance when you need it most.

**40%**

Up to 40% energy  
use reduction with  
water cooling

# The Danfoss way

For decades, our fluid conveyance experts have helped shape and evolve the direct-to-chip liquid cooling market, delivering high-performance source line and rack cooling solutions, while keeping ease of installation and service a priority.



## One partner, every solution

Danfoss has a comprehensive portfolio of premium fluid conveyance products to meet your thermal management system needs. With products designed to work in concert, we'll deliver everything you need for a high-performing source-to-rack cooling solution.

## Creative design solutions are our specialty

With optional configurations, Danfoss' fluid conveyance solutions offer the flexibility you need to design the ultimate data center. Our products are designed to work in tight spaces to simplify installation and maintenance, ensuring your cooling system operates efficiently.

## Making cutting-edge simple

Peace of mind and resiliency — that's what Danfoss liquid cooling systems bring to your data center design. Whether it's hoses with the highest-level flame rating available (UL94 V0), or individually leak-tested dry-break couplings, Danfoss delivers market-leading technology optimized for performance and reliability.

## Experts everywhere

We are your liquid cooling experts. We pioneered leak-free, quick disconnect technology with IBM decades ago and remain at the forefront of the industry today. And with a global team embedded in all major regions of the world, our extensive knowledge ensures each customer has what they need to be successful.



**OPEN**  
Compute Project  
SOLUTION PROVIDER®

## A member of OCP

Danfoss is a Solution Provider of the Open Compute Project (OCP), a collaborative, community-focused organization working to standardize the design and performance of all hardware for small- to hyper-scale data centers. We're not just meeting the industry standard; we're helping set it, both today and into the future.

# Making connections **you can count on.**

From main supply lines to single point connections, Danfoss provides the hardware to make your software work.



**Danfoss Hansen®  
FD83 Series**  
Full-flow dual-interlock  
coupling

An industry standard, our stainless steel FD83 has been supporting data center liquid cooling reliably for decades.



↑ To data center  
Cooling  
Distribution  
Unit (CDU)  
↓



**Boston by Danfoss  
Royal™ EHW194 EPDM hose**

Engineered for durability and ease of use, EHW194 hoses feature industry-leading safety ratings, superior kink resistance and long-lasting performance.



**FLUID COMPATIBILITY**



**FULL FLOW**





**EASE OF USE**






**RELIABILITY**

# Source line solutions

Every data center has different requirements. Our range of fluid conveyance solutions enable you to engineer the **safest and most efficient** thermal management system for your data center.

Couplings			
<ul style="list-style-type: none"> <li>Leak-free and corrosion resistant.</li> <li>100% helium leak tested.</li> <li>FD83 patented locking mechanism ensures parts cannot be disconnected while liquid is flowing.</li> <li>FD83 offers unlimited configuration options, eliminating extra clamps or additional components.</li> </ul>			
<b>FD83 series</b> Full-flow dual-interlock coupling Stainless steel		<ul style="list-style-type: none"> <li>303 Stainless steel or engineered plastic</li> <li>Standard seal material: EPDM</li> <li>Locking pin design and lever handle</li> <li>Identical coupling halves</li> </ul>	<ul style="list-style-type: none"> <li>Highest flow and low spillage</li> <li>100% helium leak tested</li> <li>Size: 1" and 2"</li> <li>Port Connections: 3/4", 1" and 2"</li> </ul> <b>Pairs with:</b> <ul style="list-style-type: none"> <li>FC332</li> <li>EHW194</li> </ul>
<b>MLDB series</b> Flat face, dry break coupling		<ul style="list-style-type: none"> <li>316 Stainless steel</li> <li>Standard seal material: EPDM</li> <li>Integrated pre-guiding system for easy connection</li> <li>Flat face design</li> </ul>	<ul style="list-style-type: none"> <li>Color coding available</li> <li>High flow and no spillage</li> <li>Sizes: 1/4" to 1"</li> <li>Sizes for source line and inner rack installations</li> </ul> <b>Pairs with:</b> <ul style="list-style-type: none"> <li>FC332</li> <li>EHW194</li> <li>GH109</li> </ul>



Hoses			
<ul style="list-style-type: none"> <li>Full, unrestricted flow and excellent kink resistance.</li> <li>Multiple size and specification options to meet your requirements.</li> <li>Hoses with UL94 V0 rating — leads the industry.</li> <li>Tested with wide range of industry standard coolant solutions to ensure compatibility with corrosion inhibitors, eliminating contamination and ensuring long life.</li> </ul>			
<b>FC332</b> Socketless hose		<ul style="list-style-type: none"> <li>CPE tube and cover, textile braid reinforcement</li> <li>UL94 HB compliant</li> <li>Excellent kink resistance</li> </ul>	<ul style="list-style-type: none"> <li>Operating temperature: -40°C to +150°C (-40°F to 302°F)</li> <li>Sizes: -04, -06, -08, -10, -12</li> </ul>
<b>Boston Royal EHW194</b> Rubber hose		<ul style="list-style-type: none"> <li>EPDM tube and cover, two-ply textile reinforcement</li> <li>UL 94 V-0 rated</li> <li>Smooth, kink resistant hose with tight bend radius for routing</li> <li>Qualified with push-on &amp; crimp fitting options</li> </ul>	<ul style="list-style-type: none"> <li>Multiple color options</li> <li>Operating temperature: -40°C to +140°C (-40°F to 284°F)</li> <li>Sizes -4 thru -16 (except -5)</li> <li>16 bar (232 psi)</li> <li>Available with thin-wall: smaller diameter for improved flexibility and lower bending radius</li> </ul>

Fittings			
<b>Socketless Fittings</b>		<ul style="list-style-type: none"> <li>Brass or stainless steel</li> <li>Configurable end connections available</li> <li>No tools needed</li> <li>No clamps required</li> </ul>	<ul style="list-style-type: none"> <li>Qualified with FC332, GH109 and EHW194 hoses</li> </ul>

# Solutions to your **liquid cooling challenges.**



OCP  
INSPIRED™



**Danfoss UQD**  
Universal quick disconnect  
coupling

Designed for high flow rate and no spillage, the UQD coupling is perfect for in-rack applications with smaller hose lines.



**Boston by Danfoss**  
**Royal™ EHW194 EPDM hose**

Engineered for durability and ease of use, EHW194 hoses feature industry-leading safety ratings, superior kink resistance and long-lasting performance.


**Danfoss Blind-Mate**  
Hands-free self-centering  
quick disconnect coupling

The Blind-Mate's self-centering design offers misalignment compensation, ensuring simple and secure connection between the blade and rack manifold.



**Danfoss UQD Blind-Mate**

Offers a self-alignment feature to help connect in location with limited access or visibility and guarantees 100% helium-leak testing on every coupling.




Rack  
manifold

# Inner rack solutions

Danfoss' direct-to-chip cooling solutions extend into the racks through efficient routing of flexible, kink-free hoses, and leak-free, helium-tested couplings.

Couplings				
<ul style="list-style-type: none"> <li>No-leak, no-drip designs.</li> <li>Corrosion-resistant anodized aluminum, stainless steel or composite plastic options.</li> <li>Deliver high flow and low pressure drop.</li> </ul>				
<b>OCP ORV3 BMQC</b> Hands-free self-centering quick disconnect coupling		<ul style="list-style-type: none"> <li>303 stainless steel</li> <li>EPDM seal</li> <li>Self-centering design with radial, angular and axial misalignment compensation</li> <li>Designed for hands-free connection</li> </ul>	<ul style="list-style-type: none"> <li>Interchange meets OCP standard</li> <li>100% helium-leak tested</li> <li>Sizes: 3mm</li> </ul>	<b>Pairs with:</b> • EHW194 • GH109
<b>ADB</b> Flat face/dry break couplings		<ul style="list-style-type: none"> <li>Aluminum</li> <li>EPDM seal</li> <li>Integrated pre-guiding system for connection</li> <li>Flat face design</li> </ul>	<ul style="list-style-type: none"> <li>Color coding available</li> <li>High flow and no spillage</li> <li>Sizes: ¼" to 1"</li> <li>Available in stainless steel (MLDB)</li> </ul>	
<b>UQD</b> Universal quick disconnect coupling		<ul style="list-style-type: none"> <li>303 and 304 stainless steel</li> <li>EPDM seal</li> <li>Push-to-connect design</li> <li>Meets OCP performance specifications</li> </ul>	<ul style="list-style-type: none"> <li>High flow and no spillage</li> <li>100% helium leak tested</li> <li>Sizes: UQD02, UQD04, UQD06, UQD08</li> </ul>	
<b>UQDB</b> Universal quick disconnect blind-mate		<ul style="list-style-type: none"> <li>303 stainless steel</li> <li>EPDM seal</li> <li>Meets OCP performance specifications</li> </ul>	<ul style="list-style-type: none"> <li>Blind-connection thanks to self-alignment feature with radial compensation of 1 mm</li> <li>Sizes: UQDB04. Sizes -02/-06/-08 coming soon.</li> </ul>	

Hoses				
<ul style="list-style-type: none"> <li>Hose with UL94 V0 rating — leads the industry.</li> <li>Best-in-class rubber hose</li> </ul>				
<b>Boston Royal EHW194</b> Rubber hose		<ul style="list-style-type: none"> <li>EPDM tube and cover, two-ply textile reinforcement</li> <li>UL 94 V-0 rated</li> <li>Smooth, kink resistant hose with tight bend radius for routing</li> <li>Qualified with push-on &amp; crimp fitting options</li> </ul>	<ul style="list-style-type: none"> <li>Multiple color options</li> <li>Operating temperature: -40°C to +140°C (-40°F to 284°F)</li> <li>Sizes -4 thru -16 (except -5)</li> <li>16 bar (232 psi)</li> <li>Available with thin-wall: smaller diameter for improved flexibility and lower bending radius</li> </ul>	

# Refrigerant solutions

Always innovating and evolving to deliver the latest in liquid cooling technology, Danfoss' refrigerant solutions meet the needs of the next generation of data center.

Refrigerant solutions				
<b>GH001 &amp; EZ Clip Fittings</b>		<ul style="list-style-type: none"> <li>Thermoplastic veneer lining with elastomeric tube, synthetic elastomer cover, textile reinforcement</li> <li>Lowest permeation assembly on the market</li> <li>Maximum kink resistance and qualified at full vacuum</li> </ul>	<ul style="list-style-type: none"> <li>R134a, R1234yf, R407C, R404A, R12, 1234ze, 1233zd and other refrigerants</li> <li>Sizes: -4, -6, -8, -10, -12, -16</li> </ul>	

# Fluid conveyance **solutions for liquid cooling** data centers

Efficient • Reliable • Sustainable

Count on Danfoss' data center experience to help lead the future of data center liquid cooling

Delivering industry-leading solutions with decades of proven performance, Danfoss' global team of fluid conveyance experts continually advance liquid cooling technology to enable the data center of tomorrow.



**Beijing Hansen Fluid Technology Co., Ltd.**  
**Danfoss Data center liquid cooling authorized distributor**

Add: Rm2115, Tower C, Wangjing SOHO, Chaoyang district Beijing, China

PO: 100102

Phone: 010-8428 2935, 8428 3983, 13910962635

Mobile: 15801532751, 17310484595, 13910122694  
13011089770, 15313809303

Http: //www.hansenfluid.com

E-mail: sales@cnmec.biz

For more information visit:

**[danfoss.com/data-center-liquid-cooling](https://danfoss.com/data-center-liquid-cooling)**

Danfoss can accept no responsibility for possible errors in catalogues, brochures and other printed material. Danfoss reserves the right to alter its products without notice. This also applies to products already on order provided that such alterations can be made without subsequential changes being necessary in specifications already agreed. All trademarks in this material are property of the respective companies. Danfoss and the Danfoss logotype are trademarks of Danfoss A/S. All rights reserved.